



# KlinMak<sup>®</sup>

keep clean

with DiSy disinfecting is easier and faster



# DiSY

## DISINFECTING MACHINE

## Description



### DiSy5 & DiSy10

The DiSy range, in the practical Trolley versions, is the ideal solution for dispensing a low wet-effect, water-based solution (micro-drops less than 30 microns in diameter) on every surface (floors, walls, doors, wardrobes, bathrooms, kitchens, tables, metal surfaces, etc.), added with a specific disinfectant (e.g., bactericidal, fungicidal or virucidal) in a variable percentage depending on the objective: decontamination-disinfection and sanitation only.

The fine, spherical nebulization allows the operator to reach distances of up to 1.5 m, easily and completely covering the surfaces to be treated. Two models, 5 and 10 liters, allow continuous operation from 30 to 60 minutes covering a total area of 1,250 to 2,500 square meters; the power supply is a lithium battery capable of ensuring operation from 2 to 4 hours and able to recharge quickly.

Portability and handling are guaranteed by the 4 wheels, with 15 meters of tubing on board together with the misting system consisting of a lance, a multi-outlet nozzle holder and nozzles.

The display is equipped with a button for activating the misting pump and a charge indicator for the battery charge status; the charger is external.

The treatment offers results through the correct use of disinfectant : type (e.g., virucidal if the main danger is coronavirus) and contact time. It is advisable to use a low residue disinfectant. Always follow the manufacturer's indications both in percentages and in the use of proper PPE.

## Main Technical Specifications

Description	u. m.	DiSy5	DiSy10
<b>Part Number</b>		F.600.0	F.650.0
Tank capacity	L	5	10
Max. productivity per hour	mq	750	1500
Treated surface per tank	mq	1250	2500
Runtime per tank		up to 30 min	up to 1h
<b>Solution supply</b>			
Nozzle flow	ml/min	200	200
Atomization micron	micron	max 30	max 30
Atomization distance	mm	0-1500	0-1500
Total length of atomization hose	m	15	15
<b>Power supply</b>			
Voltage	V	24	24
Battery	tipo 	Lithium 24V -5,6Ah	Lithium 24V -11,2Ah
Charger	A	2	5
<b>Runtime and charging time</b>			
Flow runtime	h	2	4
Battery charging time	h	2	2
<b>Other Techs</b>			
Sound Level	dbA	50	50
Packaging Dimension	mm	400x500x300	400x600x300
Weight with/without Packaging	kg	12/15	18/24

Partner



**KlinMak Srl**

Via della Levata 1 | 20084 Lacchiarella (MI) | Italy

Tel. +39 02 892929.1 | Fax +39 02 892929.90

info@klinmak.com | www.klinmak.com